

Vertical Roll Mill Series


Bevel planetary gear units for heavy duty grinding applications

Extreme industrial applications require reliable gear units all year round. Gearboxes with longer bearing life, improved power density and increased product lifecycle are key factors in the decision making process.

David Brown Santasalo's vertical roller mill series delivers power, durability and reliability even under extreme conditions.

Key benefits:

- Designed in close cooperation with manufacturers for different mill types to provide an optimal solution for each application
- Gear unit operates efficiently and transfers acting loads accurately, ensuring continuous and failure-free production flow
- Surface finishing process for advanced fatigue strength and increased wear resistance
- Profile and longitudinal modifications provide optimum tooth flank contact guaranteeing low vibration, low noise levels and longer lifecycle



Technical data	
Design Sizes	10
Number of Stages	2
Power Range	up to 4,000 kW
Transmission Ratio	20-45
Nominal Output Torque	up to 3,000 kNm

Cement

Chemicals

Defence

Fibre, paper & tissue

Food & beverage

Marine & port operations

Metals

Mining & minerals

Oil & gas

Panelboard


Power generation

Rail

Rubber

Sugar

Water & wastewater



Approved lubrication unit

The gear unit is lubricated by a closed circuit oil system. All assemblies and components such as motor pumps (high and low pressure), the switchable double oil filter, oil cooler and instrument panel are installed on the oil tank platform. The lubricant system is standardised across several types of gear units, ensuring easy handling, optimal insertion and lower costs. To ensure operational reliability, the entire oil and cooling system is monitored and controlled via a Programmable Logic Controller (PLC) on site.

Axial thrust bearing

The optimum design and layout of the axial thrust bearing ensures high operational safety. The innovative design of the slide bearing pads ensures reliable operation. Axial thrust bearing layout is evaluated based on the required thickness of the lubrication film and therefore as a function of the geometry of the pads, load, circumferential speed and oil viscosity.



Europe

Finland: finland@dbsantasalo.com

France: france@dbsantasalo.com

Germany: germany@dbsantasalo.com

Russia: russia@dbsantasalo.com

Sweden: sweden@dbsantasalo.com

Turkey: turkey@dbsantasalo.com

UK: uk@dbsantasalo.com

Asia Pacific

Australia: australia@dbsantasalo.com

China: suzhou@dbsantasalo.com

India: india@dbsantasalo.com

Indonesia: indonesia@dbsantasalo.com

Malaysia: malaysia@dbsantasalo.com

Philippines: philippines@dbsantasalo.com

Americas

Canada: canada@dbsantasalo.com

Chile: chile@dbsantasalo.com

Peru: peru@dbsantasalo.com

USA: usa@dbsantasalo.com

Africa

South Africa: salessa@dbsantasalo.com

www.dbsantasalo.com

GearWatch Condition
Monitoring:

